

DECODALLE CORK WALL TILES

TECHNICAL SPECIFICATION

General definition and product composition		
Definition		Veneered agglomerated cork tiles to be used as wallcoverings within buildings. Tiles are produced by gluing one decorative cork veneer with one backing of agglomerated cork. Tiles are cut in the dimensions of 600 x 300 mm and have a thickness of 3 mm. The surface is fine sanded and finished with wax.
Dimensions		600 x 300 x 3 mm
Product structure and materials		Granulated cork, broken cork and/or pieces of cork of different sizes, shapes and qualities depending on the design type; Polyurethane cork binder; Waterbased adhesive (PVA); Hot-melt wax as finishing.
Installation system		Glued
Technical data		
Length and width	EN ISO 24341	600 x 300 mm ± 0.4 %
Overall thickness	ISO 7322	3 mm ± 0.2 mm
Squareness Straightness	EN ISO 24342	< 0.4 mm < 0.25 mm
Apparent density	ISO 3850	220 Kg/m ³
Mass per unit area	EN ISO 23997	700 g/m ² ± 10 %
Tensile strength	ISO 7322	> 300 kPa
Compression Recuperation	ISO 7322	< 40 % > 75 %
Dimensional variation	EN ISO 23999	< 0.4 %
Moisture content	EN 12105	< 8 %
Curling	EN ISO 23999	< 6 mm
Reaction to fire	EN 13501-1	Fire class E
Formaldehyde emission	EN 12149	Below Detection Limit No formaldehyde-containing products are added during the manufacturing.

DECODALLE CORK WALL TILES

TECHNICAL SPECIFICATION

Technical data		
Heavy metals and specific elements Arsenic; Barium; Cadmium; Chromium; Mercury; Lead; Antimony; Selenium	EN 12149	Fulfilled None of these substances are added or have come in direct contact with the product during the manufacturing process
Release of vinyl chloride monomer	EN 12149	Below Detection Limit
Thermal resistance	EN 12667	0.06 (m ² .K)/W
Sound absorption	ISO 354	α _w 0.05
General data		
Features		Safe and easy to handle and install; Effective reduction of airborne sound; Increases the thermal comfort; Persistence of characteristics along time; Without the release of toxic gases when burning; Lightweight, flexible and odourless; No harmful chemicals; Natural, biodegradable and recyclable product;
Packaging		DECODALLE tiles are packed in cardboard cartons, each containing 8 packs wrapped in shrinking foil, providing suitable protection for normal transport and storage conditions. Cartons are identified by a label and/or inkjet printing and palletized. Each pallet is over strapped and wrapped with stretch film. Tiles per carton: 88 Sqm per carton: 15.84 m ² Weight per carton: 12 Kg Cartons per pallet: 42 Sqm per pallet: 665.3 m ²
Environment		DECODALLE tiles are made using more than 90% cork, which is a renewable raw material. It contains no PVC and no softeners or other substances hazardous to health or the environment.



GRANORTE reserves the right to make changes to material and structure to improve the quality or technical performance.