

# 849 U 842 F

## SEAMTAPE

---

### PRODUCT DESCRIPTION

---

High quality, tear-resistant underlay polyester fleece tapes for bonding artificial turf along the seams, in combination with Eurocol artificial turf adhesives.

842 Eurotape F seam tape for football fields  
849 Eurotape U seam tape universal

---

### PRODUCT FEATURES

---

- very high tensile strength

---

### TECHNICAL DATA

---

Base	849 U: two-layer polyester-fibre-based non-woven 842 F: three layer polyester fibre - polypropylen-fibre-based non-woven
Colour	white
Thickness	849 U: 0,43 mm 842 F: 0,41 mm
Width	30 cm
Weight	849 U: approx. 170 g/m <sup>2</sup> 842 F: approx. 185 g/m <sup>2</sup>
Tensile strength	849 U: approx. 380 N/ 5 cm 842 F: approx. 920 N/ 5 cm
Permitted shelf-life	within approx. 72 months,
Storage condition	packaging to be tightly closed at a dry place, temperature: 5 - 30 °C
Code acc. to GHS	no

---

### FLOOR PREPARATION

---

The sub-floor must be well prepared for installing artificial grass covering on it, above all it must be even and dry.

---

### INSTRUCTIONS FOR USE

---

The sheets of the artificial grass need to be laid on the sub-floor side by side without tension (but no overlapping!). Fold the seams back, place Eurocol Eurotape underneath the artificial grass right in the middle of the seams. Apply Eurocol 149 Euomix Turf or 160 Euomix Turf Pro, install the artificial grass into the adhesive and rub it down.

# 849 U – 842 F

## Eurotape

After the adhesive has been cured, it is possible to put sand on the artificial grass.

---

### NOTE

---

Relevant norms and regulations of the branch are to be respected. Outside Germany relevant national regulations are to be applied which must be known by the user.  
Please pay attention to the technical data sheet and safety data sheets of auxiliary materials.

---

### PACKAGING

---

849 U rolls 100 lm, 60 / palette

842 F rolls 100 lm, 55 / palette

---

### SPECIAL NOTE

---

Any application method/conditions other than specified in this Technical data sheet require explicit manufacturer's approval. In case of deviance in application method/conditions liability by manufacturer cannot be guaranteed.

This technical data sheet contains advice on handling and application of the product, based on experience and tests run by the manufacturer in laboratory and practical work.

The information supplied by the manufacturer are non-binding and cannot be used as a basis for establishing the manufacturers liability for any damages caused. The values stated in this technical data sheet were measured under standard laboratory conditions.

As application conditions outside the laboratory vary strongly this technical data sheet must be considered a guide only. Therefore, the manufacturer does not take liability for damages caused by the customer's utilization of the technical data sheet content.

As the usage, processing- and storage conditions on site are beyond the manufacturers influence, a warranty for the processing result cannot be given. This also includes the infringement of any rights for the protection of third parties. Sufficient testing areas are to be provided before final application. Relevant national norms and regulations of the industry are to be observed. Outside Germany valid, relevant national norms and regulations, must be taken into account and to follow by the customer. It is the responsibility of the customer to check product suitability for the intended procedure and purposes prior to use. This Technical Information supersedes all previously issued application data sheets and product information are no longer valid!

Technical information and Material Safety Data Sheets of concomitantly used installation materials must be followed carefully.

The products delivered by the manufacturer are for professional use only. Keep away from children.

The manufacturer's terms and conditions are binding.

Last updated 25.4.2019  
Supersedes issue as of 16.6.2014

Version Nr.:03  
BG144502\_849-842-HW001