


Gauge	3/16	
Manufacturing	Cut pile	
Pile description	PP Twistex 2-ply	
Primary backing	Woven	
Pile weight	875 gr/m ²	
Number of tufts	50.393 /m ²	
Secondary backing	Premiumback	
Width	400 cm	500 cm
Total weight	1883 gr/m ²	1883 gr/m ²
Total height	22 mm	22 mm
Pile In/Out	Out	Out
Roll length	25 m	25 m
DOP	1087#781/XAS/H	
Fire classification	Efl	
Use classification	22	
TOG rating	1,2	

Available colours Premiumback | 400/500 cm 109 | 139 | 166 | 224 | 303 | 307 | 314 | 338 | 884 | 990 |

Colour legend	109 Steel	139 Phantom	166 Iron
	224 Jade	303 Oyster	307 Ivory
	314 Mink	338 Caramel	884 Aqua
	990 Fondant		



These details are approximate. Complete specification details and associated certificates together with tolerances applying to the above can be provided upon request. We reserve the right to modify technical specifications without prior notice. Due to method of manufacture perfect pattern and/or colour matching can not be guaranteed. In cut-pile carpeting, in rare cases, shading/pile reversal may occur without affecting its fitness for use. Shading/pile reversal can not be considered as a manufacturing or a material defect and will not affect the durability of the carpet.

BIG Floorcoverings nv Rijksweg 442 | 8710 Wielsbeke - Belgium | T +32 (0)56 67 42 11 | F +32 (0)56 67 48 40 | www.ideal-bintg.com

16.10.2018 | ISO N090N02/2/01-01-10



109 - 400/500 cm



139 - 400/500 cm



166 - 400/500 cm



224 - 400/500 cm



303 - 400/500 cm



307 - 400/500 cm



314 - 400/500 cm



338 - 400/500 cm



884 - 400/500 cm



990 - 400/500 cm