
EUROSTRIP BASIC 802

Sound insulation tape

Properties: Self adhesive
Constant elastic.
Does not rot.
Allows moisture transference.
For use as sound transfer barrier between floors and walls in combination with 965 Europlan Flex on wooden floor construction.

Technical Data:	Base:	PE foam
	Thickness:	5mm
	Height:	20mm
	Length:	25m

Instruction for use: Remove the protective plastic band from the 802 and stick to the floor/wall, the surface should be free from dust to ensure a good bonding

Note: For the installation of screeds exceeding 20mm we recommend using the 8021 Eurostrip Profi (Sound insulation tape).

Packaging: 250m (10 rolls at 25m)

Special note: Any application method/ conditions other than specified in this Technical data sheet require explicit manufacturer's approval. In case of deviance in application method/ conditions liability by manufacturer cannot be guaranteed. This technical data sheet contains advice on handling and application of the product, based on experience and tests run by the manufacturer in laboratory and practical work. The information supplied by the manufacturer are non-binding and cannot be used as a basis for establishing the manufacturers liability for any damages caused. The values stated in this technical data sheet were measured under standard laboratory conditions. As application conditions outside the laboratory vary strongly this technical data sheet must be considered a guide only. Therefore, the manufacturer does not take liability for damages caused by the customer's utilization of the technical data sheet content. As the usage, processing- and storage conditions on site are beyond the manufacturers influence, a warranty for the processing result cannot be given. This also includes the infringement of any rights for the protection of third parties. Sufficient testing areas are to be provided before final application. Relevant national norms and regulations of the industry are to be observed. Outside Germany valid, relevant national norms and regulations, must be taken into account and to follow by the customer. It is the responsibility of the customer to check product suitability for the intended procedure and purposes prior to use. This Technical Information supersedes all previously issued application data sheets and product information are no longer valid!
Technical information and Material Safety Data Sheets of concomitantly used installation materials must be followed carefully.
