
Euroclean Handclean 815

Proerties:

- Impregnated hand cloth
- Very good cleaning and dissolving properties
- in dispensing box

For the cleaning of:

- smooth surfaces or the cleaning of tools from fresh
- silicon, PU foam, adhesives, MS polymer and paints

Plus many other contaminants.

Technical data:

Base:	Cloth impregnated with special tenside
Colour:	white
Permitted shelf-life:	approx. 12 months
Storage condition:	packaging to be firmly closed at normal temperature

Contains d-limonene, mixture of dmdm hydantoin and 3-iodo-2-propynyl butylcarbamate. May produce an allergic reaction.

Contains INCI: AQUA, ISOPROPYL ALCOHOL, DIMETHYL GLUTARATE, C9-11 PARETH-8, DIMETHYL SUCCINATE, DIMETHYL ADIPATE, PEG-75 LANOLIN, DMDM HYDANTOIN, LIMONENE, BHT, TETRASODIUM EDTA, IODOPROPYNYL BUTYLCARBAMATE.

* Above mentioned data was made in laboratory, due to a big variety of object-bound application cases, these data should be considered only as a norm.

Instruction for use: Remove a cloth from dispenser and close the dispenser immediately, remove the non hardened material, the more fresh the dirt the easier to clean, you can achieve a clean shiny surface when polishing with a clean dry cloth afterwards.

Do not use on absorbent floors e.g. none sealed wood, when using on delicate surface please test before use.

The used cloths can be disposed of in house rubbish. NOT IN THE TOILET.

Packaging: Dispenser with 100 cloths, carton with 6 dispenser units

Special note: Any application method/conditions other than specified in this Technical data sheet require explicit manufacturer's approval. In case of deviance in application method/conditions liability by manufacturer cannot be guaranteed. This technical data sheet contains advice on handling and application of the product, based on experience and tests run by the manufacturer in laboratory and practical work. The information supplied by the manufacturer are non-binding and cannot be used as a basis for establishing the manufacturers liability for any damages caused. The values stated in this technical data sheet were measured under standard laboratory conditions. As application conditions outside the laboratory vary strongly this technical data sheet must be considered a guide only. Therefore, the manufacturer does not take liability for damages caused by the customer's utilization of the technical data sheet content. As the usage, processing- and storage conditions on site are beyond the manufacturers influence, a warranty for the processing result cannot be given. This also includes the infringement of any rights for the protection of third parties. Sufficient testing areas are to be provided before final application. Relevant national norms and regulations of the industry are to be observed. Outside Germany valid, relevant national norms and regulations, must be considered and to follow by the customer. It is the responsibility of the customer to check product suitability for the intended procedure and purposes prior to use. This Technical Information supersedes all previously issued application data sheets and product information are no longer valid! Technical information and Material Safety Data Sheets of concomitantly used installation materials must be followed carefully. The products delivered by the manufacturer are for professional use only. Keep away from children.

eurocol – the strong connection

eurocol

Geschäftsführer: Dr. rer. nat. Stefan Vollmuth,
Jochen Schwemmler
Handelsregister HRB 100351 Jena (D)
Ust.IdNr. DE 811 178 280

Forbo Eurocol Deutschland GmbH
August-Röbling-Straße 2
99091 Erfurt, Germany

Phone +49 361 7 30 41-0
Fax +49 361 7 30 41-90
info.erfurt@forbo.com
www.forbo-eurocol.de