

232

MOUNTING ADHESIVE

PRODUCT DESCRIPTION

Elastically curing mounting adhesive, allows materials to be positioned for accurate alignment especially for installation of wooden or hard-vinyl skirting boards. Also used for joint sealing and installation of chip and gypsum-boards, gypsum plasterboards, insulation and acoustic panels. For installation of construction boards, window seats made of plastic, natural stone or composite materials. Excellent adhesion properties on concrete, wood materials, clean metal surfaces. Not for styropor. Hazardous materials: please check safety data sheet!

GISCODE S 1

PRODUCT FEATURES

Ready-to-use, high viscosity with joint filling properties. Creates a flexible adhesive ridge (after curing)

Temperature resistant from -20°C to 60°C. Contains solvent.

TECHNICAL DATA

Base	synthetic rubber
Color	white
Density	approx. 1,26 g/cm ³
Consistency	paste-like
Cleaning agent	white spirit, acetone
Processing conditions	not below 15 °C on the subfloor, minimum 18°C material- and room temperature 35-75% relative air moisture, recommended <65%, at least 3°C above dew point
Mode of application	cartidge pistol
Adhesion time	approx. 10 min
Curing time	2-4 days, depending on the adhesive layer thickness and the room temperature
Consumption	Approx. 20 - 40 ml/rm,
Permitted shelf-life	within approx. 12 months, opened packaging to be tightly closed and to be consumed as soon as possible.
Storage condition	packaging to be tightly closed at a dry place, temperature: 5 - 30 °C.
Frost sensitivity	no.
FFlammability	yes
Code acc. to GHS	yes, pay attention to the safety data sheet
Enviroment/Work safety	GISCODE: S1

232

Eurosol Montage

SUBFLOOR

The subfloor must be dry and free of oil residues and dust. Smooth surfaces must be degreased and cleaned. Porous, sandy surfaces must be brushed up to the load-bearing layer and might be primed with Eurocol 044 Europrimer Multi Plus (diluted with water 1:2). Drying time: approx. 2-3 hours. meet the requirements according to national standards, regulations and norms.

INSTRUCTIONS OF USE

Remove the lid of the cartridge edge and cut the membrane of the cartridge exit off. Screw the top of the nozzle off and cut it according to the desired width.

Apply the adhesive as dots or waves on the backing of the material or on the subfloor. The amount of adhesive depends on how even the subfloor is. Press both sides together immediately to get the adhesive on both sides, separate both sides again, allow them to rest for 5-10 min, press them together and rub them down well. Pressing both sides together should be done before the adhesive develops a skin, otherwise the adhesion power cannot be guaranteed.

Please pay attention to the technical data sheet of auxiliary material!

NOTE

Eurocol 232 Eurosol montage contains hazardous ingredients. **Please pay attention to the safety data sheet!**

PACKAGING

cartridge 310 g net – 12 cartridges/card-board bo

SPECIAL NOTE

Any application method/ conditions other than specified in this Technical data sheet require explicit manufacturer's approval. In case of deviance in application method/ conditions liability by manufacturer cannot be guaranteed.

This technical data sheet contains advice on handling and application of the product, based on experience and tests run by the manufacturer in laboratory and practical work.

The information supplied by the manufacturer are non-binding and cannot be used as a basis for establishing the manufacturers liability for any damages caused. The values stated in this technical data sheet were measured under standard laboratory conditions.

As application conditions outside the laboratory vary strongly this technical data sheet must be considered a guide only. Therefore the manufacturer does not take liability for damages caused by the customer's utilization of the technical data sheet content.

As the usage, processing- and storage conditions on site are beyond the manufacturers influence, a warranty for the processing result cannot be given. This also includes the infringement of any rights for the protection of third parties. Sufficient testing areas are to be provided before final application. Relevant national norms and regulations of the industry are to be observed. Outside Germany valid, relevant national norms and regulations, have to be taken into account and to follow by the customer. It is the responsibility of the customer to check product suitability for the intended procedure and purposes prior to use. This Technical Information supersedes all previously issued application data sheets and product information are no longer valid!

Technical information and Material Safety Data Sheets of concomitantly used installation materials must be followed carefully.

The products delivered by the manufacturer are for professional use only. Keep away from children.
The manufacturer's terms and conditions are binding

Stand 20. November 2018
ersetzt Ausgabe vom 17 December 2007

Version Nr.: 04
BG113100_232-02