

898 Longlife

LOGLIFE BASIC PROTECTION

PRODUCT DESCRIPTION

Hard wearing, self-shiny, dirt repelling highly resilient maintenance agent for full area refreshment of worn floor coverings. Initial and regular care of manually sealed parquet, cork floor coverings, resilient floor coverings is subject to manufacturer's instructions. Dries to a slip and stain resistant protective film.

To use for refreshing of used, waterproof floorings and after careful base cleaning.

No polishing needed.

Can be used as a water additive for the maintenance of parquet and cork sealed by hand with water-based varnish, for PVC, CV and linoleum coverings without special factory PUR coating.

Different gloss levels available such as gloss and matt.

GISCODE GU 20

PRODUCT FEATURES

- forms a dirt-repellent polymer film
- prolongs the lifecycle of the floor covering / parquet varnish
- regenerates the existing coating during maintenance care and fills slight scratches

Anti-slip and dirt-repellent, resistant to scuff-marks.

AREAS OF USE



Protection agent suitable for:

- initial care of water-resistant floor coverings e.g. sealed parquet, linoleum, PVC, (plastic coating coat for surface protection)
- Initial care of manually sealed (with aqua lacquer) parquet and cork
- refreshing old, water-resistant floor coverings and old plastic coating coats

Can be used as a water additive for the maintenance of parquet and cork sealed by hand with water-based varnish, for PVC, CV and linoleum coverings without special factory PUR coating.

NOT for use on rubber, on floor coverings/parquet with PU and UV sealants

TECHNICAL DATA

Base

polyacrylate

898

Euroclean Longlife

Colour	milky
Density	approximately 1,02 g/cm ³
pH-Value	8 – 9 (depending on gloss level)
Cleaning agent	water (fresh 898) 891 Euroclean Basic (dried 898)
Processing conditions	not below 15 °C on the subfloor material- and room temperature not below minimum 18°C material- and room temperature 35-75% relative air moisture, recommended <65%,
Consumption	1 l for approximately 40 m ² (1 coat) Maintenance: 0,15 l diluted in 5 l mop water
Shelf-life	within 24 months if stored in its original packing once opened packaging to be tightly closed and product to be used as soon as possible
Frost resistance	no
Storage condition	packaging to be tightly closed at a dry place, temperature: (5 – 30) °C,
Code acc. to GHS	no
Environment/Work safety	GISCODE: GE20 DGNB: VOC 2,9 - 5,0 %, quality level: 3, depending on the degree of gloss LEED: VOC 30 - 52 g/l, depending on the degree of gloss Mat: Contains: 5-Chlor-2-methyl-2H-isothiazol-3-on. May cause allergic reaction. Gloss: Contains 1,2-Benzisothiazol-3(2H)-on. May cause allergic reaction.

INSTRUCTIONS FOR USE

- Shake well before use in order to achieve an equally matt finish on the whole floor.
- After professional cleaning with e.g. Eurocol 891 Euroclean Basic, please use wipe with fresh, clean water.
- Then 898 Euroclean Longlife is to be applied with a lint-free cloth or wipe undiluted once or twice.
- Please apply 898 Euroclean Longlife onto the floor always in one operation to avoid overlapping.
- For absorbent floors and floors with open pores, several coats of 898 Euroclean Longlife might be necessary to get a closed film of 898 Euroclean Longlife.
- The drying time of each coat at normal room climate is 1 – 3 hours (ready for foot traffic).
- If heavy traffic is to be expected, approximately 12 hrs. Drying time over night is recommended. *
- Refreshing old floors: Please make sure that the old floors are free of cleaning product residues (professional base cleaning has to be carried out). Afterwards please wipe the floor off twice with cold, fresh water. Before applying 898 Euroclean Longlife, allow the floor to dry for a minimum of 12 – 24 hours.

SAFETY NOTE

Pay attention to the technical information and safety data sheets of the used floorings and parquets.
Initial care of lacquered parquet can only be done once the lacquer has completely dried.
Initial care of elastic floor coverings should be done prior to start of traffic.
Please pay attention to the care instruction for maintenance care.
Old residues of 898 Euroclean Longlife have to be removed with Eurocol 891 Euroclean Basic (professional cleaning).
Not for the treatment of elastic floor coverings/parquet with PUR coating and parquet or cork floors with UV-varnishes on top.

* The guaranteed properties, such as soiling behaviour and moisture resistance, are achieved after 12 - 24 hours, depending on the number of applications of the care product. Until then the surface must be protected from moisture.

Relevant norms and regulations of the branch are to be respected.
Outside Germany relevant national regulations have to be applied which have to be known by the installer.

PACKAGING

2,5 l nonreturnable package (8/carton, 120/pallet)
5,0 l nonreturnable package (96/pallet)

SPECIAL NOTE

Any application method/ conditions other than specified in this Technical data sheet require explicit manufacturer's approval. In case of deviance in application method/ conditions liability by manufacturer cannot be guaranteed.

This technical data sheet contains advice on handling and application of the product, based on experience and tests run by the manufacturer in laboratory and practical work.

The information supplied by the manufacturer are non-binding and cannot be used as a basis for establishing the manufacturers liability for any damages caused. The values stated in this technical data sheet were measured under standard laboratory conditions. As application conditions outside the laboratory vary strongly this technical data sheet must be considered a guide only. Therefore the manufacturer does not take liability for damages caused by the customer's utilization of the technical data sheet content.

As the usage, processing- and storage conditions on site are beyond the manufacturers influence, a warranty for the processing result cannot be given. This also includes the infringement of any rights for the protection of third parties. Sufficient testing areas are to be provided before final application. Relevant national norms and regulations of the industry are to be observed. Outside Germany valid, relevant national norms and regulations, have to be taken into account and to be followed by the customer. It is the responsibility of the customer to check product suitability for the intended procedure and purposes prior to use. This Technical Information supersedes all previously issued application data sheets and product information are no longer valid!

Technical information and Material Safety Data Sheets of concomitantly used installation materials must be followed carefully.

The products delivered by the manufacturer are for professional use only. Keep away from children.

The manufacturer's terms and conditions are binding.

Last updated 2019-04-03

Supersedes issue as of 2016-02-29

Version Nr.:08
BG175225-004_898